

NovaBACKUP®

Virtual Dashboard

User Manual



NovaBACKUP / February 2022


NovaBACKUP Virtual Dashboard	3
Introduction	3
Virtual Dashboard for VMware Hypervisors	4
Adding a VMware Hypervisor	4
Editing a VMware Hypervisor	6
Removing a Hypervisor	8
Backing up Virtual Machines	9
Creating and Configuring a Backup Job	10
Restoring a Backup	14
VMware Replication	17
Setting up VMware Replication	18
Virtual Dashboard for Hyper-V Hypervisors	21
Adding a Hypervisor	21
Editing a Hyper-V Hypervisor	23
Removing a Hypervisor	25
Backing up Hyper-V Hypervisors	26
Creating a Backup Job for a Hyper-V Hypervisor	27
Restoring a Hyper-V	31
Hyper-V Replication	35
Setting up Hyper-V Replication	35

NovaBACKUP Virtual Dashboard

Introduction

The Virtual Dashboard is where all VMware and Hyper-V backups that are capable of restoring individual files take place. It is also the center of VMware and Hyper-V replication operations. These backups are not the same as backups that are done through the Backup tab.

In order to access the Virtual Dashboard users will need to start NovaBACKUP and then click the "Virtual Dashboard" from the "Home" tab.




Virtual Dashboard for VMware Hypervisors

Adding a VMware Hypervisor

Upon opening the Virtual Dashboard, users will be prompted with the option to add a hypervisor.

Click the **Add** ("+") button at the top of the Hypervisor's menu.



Once clicking "**Add**" users will be prompted to enter information relating to their hypervisor.

Select VMware, then continue to enter the following:


Display Name: This is the friendly name for the hypervisor. This can be anything and is designed for ease of use.

Hostname / IP Address: The Hostname or IP address of the VMware ESXi or vCenter application


Username: The username with access to the ESXi or vCenter application

Password : The password for the user

Test / Save: Test the provided configuration or Save the provided configuration. Clicking Save will also test the credentials.



Once the VMware hypervisor is added, you can then select the individual Virtual Machines that you want to run a backup and restore on.




To create a backup job, you must select the individual Virtual Machine once it pops up on the right side of the screen by selecting the panel that is associated with it.

Example: Clicking on the panel "AB-WIN07" above will select that particular Virtual Machine.

Editing a VMware Hypervisor

To edit a hypervisor, click "Edit" after selecting the hypervisor to be edited under the "Select machines to protect" list.





Once a user is in the "**Edit**" menu of Virtual Dashboard, select VMware. Users will then have four options that are already filled out with preexisting information from the initial addition of the Hyper-V hypervisor.

A screenshot of a mobile application interface for editing a VMware hypervisor. At the top left is a back arrow icon with the text 'Back' below it. Below this is a 'Hypervisor Type' dropdown menu showing 'VMware'. Next is a 'Display Name' dropdown menu showing 'Vsphere'. Below that is a 'Hostname/IP Address' dropdown menu also showing 'Vsphere'. Then is a 'Username' text field containing 'username'. Below that is a 'Password' text field containing seven asterisks. At the bottom are two blue buttons: 'Test' and 'Save'.

Display Name: This is the friendly name for the hypervisor. This can be anything and is designed for ease of use.

Hostname / IP Address: The Hostname or IP address of the VMware ESXi or vCenter application

Username: The username with access to the ESXi or vCenter application


Password: The password for the user

Test / Save: Test the provided configuration or Save the provided configuration. Clicking Save will also test the credentials.


A user may then alter that information in order to edit the VMware hypervisor.

Removing a Hypervisor

To remove a hypervisor, click "Remove" after selecting the hypervisor to be edited on the "select machines to protect" list.



Note: Removing a Hypervisor will remove all protected virtual machines and their backups from the Virtual Dashboard. Remove a virtual machine removes the ability to restore that virtual machine through the Virtual Dashboard. The following window will pop up ensuring a deletion is desired.





Backing up Virtual Machines

After adding a specific virtual machine to the list of protected virtual machines, users are able to create backup jobs that are capable of restoring individual files directly back into the hypervisor.

When creating a backup job, files will be stored in a hierarchical folder structure rather than a single file. After selecting a target folder on the user's machine, the Virtual Dashboard will automatically create another folder labeled NovaBACKUP underneath that folder. Users may continue to select the original destination for all future backup jobs.



Example: A user selecting C:\Backups\ may continue to select this folder for all future backup jobs. After the first backup job runs, users will see a separate folder:
C:\Backups\NovaBACKUP\

VMware backups can be performed from any Windows 7 or Server 2008 R2 machine or greater.

Creating and Configuring a Backup Job

Step 1


Click on a specific Virtual Machine and then click on the Backup tab in the top right corner.



Step 2

Create a Backup name, Select the type, and choose the Destination. Then click Next

- **Full:** A full backup is a backup of the entire virtual machine all at once. These backups can be very large in nature and users should be aware of how much storage space is available on the destination.
- **Incremental:** Incremental backup jobs are backup jobs that base themselves on the last incremental backup job run. This means each incremental job is dependent upon the previous incremental backup in order to restore any particular file.
- **Differential:** Differential backup jobs are backup jobs that base themselves on the last full backup job run. This means that each differential backup job is independent from each other and only the last full backup and the desired differential backup are required to restore a particular file.




The screenshot shows the NovaBACKUP - Virtual Dashboard interface. On the left, under the 'Hypervisors' tab, there is a list of virtual machines: 'QA - Windows Server 20', 'QA - Windows 7 Enterpri', 'QA - Windows XP SP3 2', and 'AB-WIN07'. The main area is titled 'BACKUP' and 'Job Settings'. It contains the following fields:

- Name:** A text box containing 'my backup'.
- Type:** A dropdown menu set to 'Full'.
- Destination:** A text box containing 'C:\' with a 'Browse' button to its right.
- Retention:** A toggle switch set to 'Off'.

At the bottom, there is a navigation bar with buttons: 'Cancel', 'Settings', 'Run As', 'Schedule', and 'Next'.


Step 3

Next, users may choose to run the backup job as either a current user or a specified user



Step 4

Lastly, Users may choose to schedule the job in a variety of methods. If no schedule is desired, users may toggle the "Schedule" switch in the top right to turn off the scheduler.



The screenshot displays the 'NovaBACKUP - Virtual Dashboard' window. On the left, a sidebar lists four hypervisors: 'QA - Windows Server 20', 'QA - Windows 7 Enterpri', 'QA - Windows XP SP3 2', and 'AB-WIN07', all located at '@ ag-qavcenter\QADat...'. The main area is titled 'BACKUP' and shows the 'Schedule' configuration for a selected job. At the top right of the main area is a toggle switch labeled 'On'. Below this, the 'Start Date/Time' is set to 'Thursday, August 14, 2014' at '2:55 PM'. The 'Type' of schedule is set to 'Daily'. The frequency is 'Repeated every 1 day(s), but only on...'. A grid of checkboxes shows the days of the week: Sunday (unchecked), Monday (checked), Tuesday (checked), Wednesday (checked), Thursday (checked), Friday (checked), and Saturday (unchecked). At the bottom, a navigation bar includes buttons for 'Back', 'Settings', 'Run As', 'Schedule', and 'Finish'.

NovaBACKUP - Virtual Dashboard

BACKUP

Schedule On

Start Date/Time

Thursday, August 14, 2014 2:55 PM

Type

Once Minute Hourly **Daily** Weekly Monthly


Repeated every 1 day(s), but only on...

☐ Sunday ☒ Monday ☒ Tuesday
☒ Wednesday ☒ Thursday ☒ Friday
☐ Saturday


Back Settings Run As Schedule Finish

Restoring a Backup

To restore a VMware backup, browse to the previously configured VMware backup job and click it.




On the following window, immediately below the "Run Summary" section will be a list of old and new backup job logs. Backup jobs that are still available for restore will be listed with three commands: Mount, Restore, and Log.



To restore a VMware backup, users are given two options:

Mount (individual file restore):

Clicking the "Mount" button will mount the virtual machine's virtual hard drives on the local computer as physical drives. Once the drive has been mounted a Windows Explorer will appear to browse the file structure. Additionally, if a drive is already mounted, users will be shown the current drive letter of the mounted image.




The screenshot displays the NovaBACKUP - Virtual Dashboard interface. On the left, a sidebar lists hypervisors: QA - Windows Server 20, QA - Windows XP SP3 2, QA - Windows 7 Enterpri, and AB-WIN07. The main area shows a backup summary for 'my backup' with details: Type (Backup - Full), Destination (C:\), Next Run (8/11/2014 4:30:00 PM - Daily), and Retention (None). Below this is a 'Run Summary' section showing an elapsed time of 00:13:15 and 0 errors, warnings, or messages. A table lists two mounted drives: I: and J:, both mounted on 8/8/2014. Each row includes buttons for 'Unmount', 'Restore', and 'Log'. At the bottom right, there are buttons for 'Delete Selected' and 'Clear History'.

Timestamp	Type	Mounted drives	Unmount	Restore	Log
8/8/2014 4:54:46 PM	Backup	I:	Unmount	Restore	Log
8/8/2014 4:25:32 PM	Backup	J:	Unmount	Restore	Log

Once mounted, the Mount button will switch to read "Unmount." After a user is finished restoring any requested individual files from the Virtual Machine, clicking Unmount will disconnect that virtual machine's virtual hard drive.

Restore (Restore to hypervisor):

To restore an image directly to a hypervisor a user must fill in the following information and then click Finish.



The screenshot shows the 'RESTORE' window in the NovaBACKUP - Virtual Dashboard. On the left, there is a list of hypervisors under the 'Hypervisors' tab. The main area is titled 'Job Settings' and contains the following fields:

- Destination Hypervisor:** A dropdown menu showing 'ag-qavcenter' with a blue '+' button to add a new hypervisor.
- Target VM Name:** A text field containing 'AB-WIN07'.
- VM Folder:** A dropdown menu showing 'QADatadcenter\Alice'.
- Target Datastore:** A dropdown menu showing 'ag-qaesx01-Datastor01'.

At the bottom of the window, there are two buttons: 'Cancel' and 'Finish'.

Destination Hypervisor: This is the destination, or target, hypervisor. This will display any currently configured VMware hypervisors. If the desired hypervisor has not already been configured, users may click the blue "+" sign to add a hypervisor at this time.

Target VM Name: The name of the virtual machine at its destination hypervisor.

VM Folder: The target ESXi / vCenter datastore that the user wishes to replicate this virtual machine into

Target Datastore: The target ESXi / vCenter datastore that the user wishes this VM to be replicated to

Log

This will display the information about that particular backup, including which files were backed up and the duration of the job.



VMware Replication

VMware replication uses the NovaBACKUP Backup / Copy Engine to copy data from either a single ESXi / vCenter host to itself or from one host to another.

Changed Block Tracking

Changed Block Tracking (CBT) is a VMware feature that helps perform incremental backups. After clicking on a protected virtual machine, users will see an option for CBT in the bottom right of the virtual machine's individual dashboard. Checking this box will enable CBT or show the current status of CBT on that virtual machine.

Without CBT enabled, replication jobs will be transferred in full each time the job is executed, which could increase replication time significantly.

Note: Enabling or disabling CBT may take time, as this is a VMware function change.


VMware Replication Retention

VMware backups are able to maintain a retention value in either generations (count) or days for Full or Differential backups. In order to apply retention to an Incremental backup, users will need to target the same folder as their incremental backup with a scheduled or manually run full backup job that includes a retention value.

Setting up VMware Replication


Step 1

Select an individual Virtual Machine and select the "**Replication**" button



Step 2

After clicking "**Replication**" users are presented with the following options:



The screenshot shows the NovaBACKUP - Virtual Dashboard interface. On the left, a sidebar lists several hypervisors: QA - Windows Server 20, QA - Windows XP SP3 2, QA - Windows 7 Enterprise, and AB-WIN07. The main area is titled "REPLICATION" and contains a "Job Settings" form. The form includes fields for Name (My VMware replication), Target VM Name (AB-WIN07_rep), Destination Hypervisor (ag-qavcenter), Target Datastore (ag-qaesx01-Datastor02), VM Folder (QADatcenter\Alice), and Retention (On, Number of recovery snapshots to keep: 3). At the bottom, there are buttons for Cancel, Settings, Run As, Schedule, and Next.

Name: The name of the backup job within the Virtual Dashboard

Target VM Name: The name of the virtual machine at its destination hypervisor. This will default to whatever the current name is plus the suffix of "**_rep**"

Destination Hypervisor: This is the destination, or target, hypervisor. This will display any currently configured VMware hypervisors. If the desired hypervisor has not already been configured, users may click the blue "+" sign to add a hypervisor at this time.


Target Datastore: The target ESXi / vCenter datastore that the user wishes this VM to be replicated to

VM Folder: The target ESXi / vCenter datastore that the user wishes to replicate this virtual machine into


Retention: The number of previously available versions stored on the target destination ESXi / vCenter. These are stored as snapshots within the ESXi / vCenter.

Step 3

Next, the following screen will prompt how you want to run the replication job as.



Step 4



Here, users may choose to schedule the job in a variety of methods. If no schedule is desired, users may toggle the "Schedule" switch in the top right to turn off the scheduler.

Virtual Dashboard for Hyper-V Hypervisors

Adding a Hypervisor


Upon opening the Virtual Dashboard users will be prompted with the option to add a hypervisor. Click the **Add "+"** button at the top of the Hypervisor's menu.

Once clicking "**Add**" users will be prompted to enter information relating to their Hypervisor.

Note: If there are already VMware hosts added through the legacy backup functionality in NovaBACKUP, those servers will already be added to the Virtual Dashboard.

Once a user is in the "**Add**" menu of the Virtual Dashboard, select Hyper-V. Users will then be presented with two options.

Adding a Local Hyper-V Hypervisor



The screenshot shows the 'NovaBACKUP - Virtual Dashboard' window. On the left is a form with the following fields:

- Back** (arrow icon)
- Hypervisor Type**: A dropdown menu with 'Hyper-V' selected.
- Display Name**: A text input field containing 'example'.
- Hostname/IP Address**: A text input field containing 'example'.
- ☐ **Connect using different credentials**
- Test** and **Save** buttons at the bottom.

The right side of the window is a large black area with a faint, stylized 'N' logo in the center.

If NovaBACKUP is being installed onto a local Hyper-V host, users will not need to enter user credentials to access the Hyper-V service. Users will need to add two fields on information as seen in the picture above.


Display Name: This is the friendly name for the hypervisor. This can be anything and is designed for ease of use.

Hostname: This is the Fully Qualified Domain Name (FQDN) or hostname of the Hyper-V host.

Test / Save: Test the provided configuration or Save the provided configuration. Clicking Save will also test the credentials.

Adding a Remote Hyper-V Hypervisor

If NovaBACKUP is being installed on a machine to manage a remote Hyper-V host, users will need to enter user credentials to access the Hyper-V service. Users will need to add four fields of information. If the Hyper-V is remote, check the "**Connect using different credentials**" checkbox.

A screenshot of the 'NovaBACKUP - Virtual Dashboard' window. The window has a dark title bar with the text 'NovaBACKUP - Virtual Dashboard' and standard window controls (minimize, maximize, close). The main content area is split into two panes. The left pane is light gray and contains a 'Back' button with a left arrow, a 'Hypervisor Type' dropdown menu with 'Hyper-V' selected, a 'Display Name' text field with 'example', a 'Hostname/IP Address' text field with 'example', a checked checkbox for 'Connect using different credentials', a 'Username' text field with 'accessusername', and a 'Password' text field with masked characters. At the bottom of the left pane are 'Test' and 'Save' buttons. The right pane is dark gray and features a large, faint, stylized 'N' logo in the background.

Display Name: This is the friendly name for the hypervisor. This can be anything and is designed for ease of use.

Hostname: This is the Fully Qualified Domain Name (FQDN) or hostname of the Hyper-V host.


Username: The local or domain username with access to the Hyper-V host

Password: The password for the user

Test / Save: Test the provided configuration or Save the provided configuration. Clicking Save will also test the credentials.


Editing a Hyper-V Hypervisor

To edit a hypervisor, click **"Edit"** after selecting the hypervisor to be edited on the "Select machines to protect" list.



Once a user is in the **"Edit"** menu of Virtual Dashboard, select Hyper-V. Users will then be presented with two options that are already filled out with preexisting information from the initial addition of the Hyper-V Hypervisor.


Editing a Local Hyper-V Hypervisor



The screenshot shows the 'NovaBACKUP - Virtual Dashboard' window. On the left, there is a configuration panel for a local Hyper-V hypervisor. The 'Hypervisor Type' is set to 'Hyper-V'. The 'Display Name' is 'ag-devhypv01'. The 'Hostname/IP Address' is also 'ag-devhypv01'. There is an unchecked checkbox for 'Connect using different credentials'. At the bottom of the panel are 'Test' and 'Save' buttons. On the right, a list of virtual machines is shown: 'Windows-XP-ag-devhypv01_3 @ ag-devhypv01' and 'Spence-Windows-XP-02 @ ag-devhypv01'. Below the list is a large black area with a faint NovaBACKUP logo.

In which a user can alter the Display Name and Hostname that were filled out in the initial addition of the Hyper-V hypervisor.


Editing a Remote Hyper-V Hypervisor



The screenshot shows the 'NovaBACKUP - Virtual Dashboard' window. On the left, there is a configuration panel for a remote Hyper-V hypervisor. The 'Hypervisor Type' is set to 'Hyper-V'. The 'Display Name' is 'ag-devhypv01'. The 'Hostname/IP Address' is 'ag-devhypv01'. The checkbox for 'Connect using different credentials' is checked. Below this, there are fields for 'Username' (containing 'example') and 'Password' (masked with asterisks). At the bottom of the panel are 'Test' and 'Save' buttons. On the right, the same list of virtual machines is shown: 'Windows-XP-ag-devhypv01_3 @ ag-devhypv01' and 'Spence-Windows-XP-02 @ ag-devhypv01'. Below the list is a large black area with a faint NovaBACKUP logo.

Here a user can alter the Display Name, Hostname, Username, Password and retest the credentials to save the provided configuration.


Removing a Hypervisor



To remove a hypervisor, click "**Remove**" after selecting the hypervisor to be edited

Note: Removing a Hypervisor will remove all protected virtual machines and their backups from the Virtual Dashboard. Remove a virtual machine removes the ability to restore that virtual machine through the Virtual Dashboard.

The following dialog will appear upon clicking "Remove" to ensure that removal of the hypervisor was intentional.





Backing up Hyper-V Hypervisors

After adding a virtual machine to the list of protected virtual machines, users are able to create backup jobs that are able to restore individual files as well as directly back into the hypervisor.

When creating a backup job, files will be stored in a hierarchical folder structure rather than a single file. After selecting a target folder on the user's machine, the Virtual Dashboard will automatically create another folder labeled NovaBACKUP underneath that folder. Users may continue to select the original destination for all future backup jobs.

Example: A user selecting C:\Backups\ may continue to select this folder for all future backup jobs. After the first backup job runs, users will see a separate folder:
C:\Backups\NovaBACKUP\

Hyper-V backups can be performed from either the Hyper-V 2012 or Hyper-V 2012 R2 host machine. Unlike VMware backups, NovaBACKUP must be installed on the Hyper-V host where the virtual machine desired to be backed up is located.

Setting up Hyper-V backups.

For Local Hyper-V connections, select the individual Hyper-V that you want to create a backup plan for and skip the following paragraph.

For remote Hyper-V connections, first connect to the remote Hyper-V by accessing the remote desktop connection and providing the hostname of the Hyper-V and your credentials to access it. From there, a user must install NovaBACKUP and access the Virtual Dashboard on the Hyper-V machine.

When creating a new backup job, users will be presented with the following options:

Name: The name of the backup job as it appears in the Virtual Dashboard

Retention: In either "Generations" (number of versions to keep or count) or "Days old" (number of days to keep available)

Run as: Users may choose to run the job as either the current user or as a specified user

Schedule: Users may choose to schedule a job in a variety of methods. If no schedule is desired, users may toggle the "Schedule" switch in the top right to turn off the scheduler.

Hyper-V Retention


Hyper-V backups can currently only be run in a full mode. Retention maintains either a Generation (count) or number of Day's

Creating a Backup Job for a Hyper-V Hypervisor

Once a user is locally connected to a Hyper-V the following steps can be taken to create a backup plan.


Step 1

Select the individual Hyper-V machine you want to create a backup job for and then select the Backup Button on the top right corner.



Step 2

After clicking the backup button, the following window will prompt users to create a backup job name and select the destination and the selection of retention.



NovaBACKUP - Virtual Dashboard

BACKUP

Job Settings

Hypervisors

- Windows-XP-ag-devhypv01 @ ag-devhypv01
- Spence-Windows-XP-02 @ ag-devhypv01

Name: testing


Destination: C:\backups\NovaBACKUP [Browse](#)

Retention: ☐ Off

[Cancel](#) [Settings](#) [Run As](#) [Schedule](#) [Next](#)


Step 3

Next a user will select how the backup job will be run



Step 4

Finally, a user will select how often they want the Hyper-V backup to occur.



The screenshot shows the 'NovaBACKUP - Virtual Dashboard' window. On the left, under 'Hypervisors', two virtual machines are listed: 'Windows-XP-ag-devhypv' and 'Spence-Windows-XP-02'. The 'Spence-Windows-XP-02' VM is selected. The main area is titled 'BACKUP' and 'Schedule'. It shows the backup is 'On' with a status icon. The 'Start Date/Time' is set to 'Monday, August 11, 2014' at '3:50 PM'. The 'Type' of backup is set to 'Hourly' (selected from a list including Once, Minute, Hourly, Daily, Weekly, and Monthly). The frequency is 'Repeated every 2 hour(s)'. At the bottom, there are navigation buttons: 'Back', 'Settings', 'Run As', 'Schedule', and 'Finish'.

NovaBACKUP - Virtual Dashboard

Hypervisors

Windows-XP-ag-devhypv
@ ag-devhypv01

Spence-Windows-XP-02
@ ag-devhypv01

BACKUP

Schedule

On

Start Date/Time

Monday, August 11, 2014 3:50 PM

Type


Once Minute **Hourly** Daily Weekly Monthly

Repeated every 2 hour(s)


Back Settings Run As Schedule Finish

Restoring a Hyper-V

To restore a Hyper-V backup, browse to the previously configured Hyper-V backup job and click it.



Immediately below the "Run Summary" section will be a list of old and new backup job logs. Backup jobs that are still available for restore will be listed with three commands: Mount, Restore, and Log.



The screenshot shows the NovaBACKUP - Virtual Dashboard interface. On the left, there is a sidebar with 'Hypervisors' and two entries: 'Windows-XP-ag-devhypv01' and 'Spence-Windows-XP-02'. The main area displays details for a backup job named 'testing'. The job details include: Type: Backup - Full, Destination: C:\backups\NovaBACKUP, Next Run: Disabled - Not Scheduled, and Retention: None. Below this is a 'Run Summary' section showing 'ElapsedTime 00:04:24' and '0 Error(s), 0 Warning(s), 0 Message(s)'. A table lists three backup operations: 8/11/2014 3:50:09 PM (Type - Backup, Mounted drives: H:), 8/11/2014 3:33:25 PM (Type - Restore), and 8/11/2014 3:01:45 PM (Type - Backup). Each row has buttons for 'Unmount', 'Mount', 'Restore', and 'Log'. At the bottom right, there are buttons for 'Delete Selected' and 'Clear History'.

Mount (individual file restore)


Click the "Mount" button will mount the virtual machine's virtual hard drives on the local computer as physical drives. Once the drive has been mounted a Windows Explorer will appear to browse the file structure. Additionally, if a drive is already mounted, users will be shown the current drive letter of the mounted image.

Once mounted, the Mount button will switch to Unmount. After a user is finished restoring any requested individual files from the Virtual Machine, clicking Unmount will disconnect that virtual machine's virtual hard drive.

Restore (Original Location)

Restoring to the original location allows a user to place the backed up copy of the virtual machine directly back in place to its original location in the Hyper-V server. This will overwrite any existing Hyper-V machines that might still be in place.

Select the Destination Hypervisor and click Finish to begin.



Restore (Alternate Location)

Restoring to an alternate location allows a user to export a copy of the backed up virtual machine to a new destination in so that it may be moves (Example: restore to USB or NAS to manually move to an alternate location).

Browse to the VHD Folder Path for the destination of the Restore and click Finish to begin.

NovaBACKUP - Virtual Dashboard

Hypervisors

Windows-XP-ag-devhypi
@ ag-devhypv01

Spence-Windows-XP-02
@ ag-devhypv01

RESTORE

Job Settings

Restore to

Hypervisor

Alternate Location

VHD Folder Path

C:\backups\NovaBACKUP

Browse

Cancel

Finish

Hyper-V Replication

Hyper-V Replication uses the Hyper-V Replica technology through Microsoft's Hyper-V service. The Hyper-V Replica technology is a block-level, asynchronous transfer from one Hyper-V host to another. After an initial full transfer, Hyper-V maintains a regularly occurring block transfer to the alternate destination.


Requirements

In order to successfully configure Hyper-V replication, users will need to properly configure their Hyper-V hosts. Hyper-V hosts must be Hyper-V 2012 or newer and all Hyper-V hosts are required to connect to a domain (for authentication purposes). Additionally, the target or destination Hyper-V server needs to be configured as a Hyper-V Replica destination.

Setting up Hyper-V Replication

Step 1

Select the individual Hyper-V that you want to replicate and then click the "**Replicate**" button on the top right.



Step 2


After clicking "**Replicate**" users are presented with the following options:

Name: The name of the backup job within the Virtual Dashboard

Replica Server: This is the destination, or target, hypervisor. This will display any currently configured Hyper-V hypervisors that are not the source Hyper-V. If the desired hypervisor has not already been configured, users may click the blue "+" sign to add a hypervisor at this time.

Retention: The number of previously available versions stored on the target Hyper-V hypervisor


Note: Replication is a single-run job type and only needs to be executed once to initialize the replication. After being configured, the Virtual Dashboard reports on the current health of the virtual machine's replication.



The screenshot shows the NovaBACKUP - Virtual Dashboard interface. On the left, a sidebar lists hypervisors: "Windows-XP-ag-devhypv01" and "Spence-Windows-XP-02-ag-devhypv01". The main area is titled "REPLICATION" and "Job Settings". It contains three fields: "Name" with the value "Windows XP Rep", "Replica Server" with the value "ag-qahypv01" and a blue "+" button to add more, and "Retention" with a toggle set to "On" and a spinner box showing "7" for the "Number of recovery snapshots to keep". At the bottom, there are five buttons: "Cancel", "Settings", "Run As", "Schedule", and "Next".


Step 3

Next a user may select how they want to run the replication job, as either the current user or a specified user.



Step 4

Lastly, users may choose a schedule for when the first initial replication takes place. If no schedule is desired, users may toggle the "Schedule" switch in the top right to turn off the scheduler.

A screenshot of the NovaBackup Virtual Dashboard. The interface has a dark header bar with the title 'NovaBACKUP - Virtual Dashboard' and window controls. Below the header, there's a sidebar on the left with a 'Hypervisors' section containing two entries: 'Windows-XP-ag-devhypv01' and 'Spence-Windows-XP-07 @ ag-devhypv01'. The main area is titled 'REPLICATION' and shows a 'Schedule' configuration for the selected hypervisor. It includes a 'Start Date/Time' field set to 'Monday, August 11, 2014' at '4:51 PM', a calendar icon, and a toggle switch labeled 'On'. At the bottom, there's a navigation bar with buttons for 'Back', 'Settings', 'Run As', 'Schedule', and 'Finish'.